§ 172.550



(b) In addition to complying with §172.519, the background color on the DANGEROUS WHEN WET placard must be blue. The letters in the words "WHEN WET" must be at least 25 mm (1.0 inches) high. The symbol, text, class number and inner border must be white.

[Amdt. 172–123, 56 FR 66263, Dec. 20, 1991]

$\S 172.550$ OXIDIZER placard.

(a) Except for size and color, the OXI-DIZER placard must be as follows:



(b) In addition to complying with §172.519, the background color on the OXIDIZER placard must be yellow. The symbol, text, division number and inner border must be black.

[Amdt. 172–123, 56 FR 66263, Dec. 20, 1991]

§ 172.552 ORGANIC Placard.

PEROXIDE

(a) Except for size and color, the OR-GANIC PEROXIDE placard must be as follows:



(b) In addition to complying with §172.519, the background color on the ORGANIC PEROXIDE placard must be yellow. The symbol, text, division number and inner border must be black.

 $[{\rm Amdt.}\ 172\text{--}123,\ 56\ FR\ 66263,\ Dec.\ 20,\ 1991}]$

§172.553 [Reserved]

§172.554 POISON placard.

(a) Except for size and color, the POI-SON placard must be as follows:




Research and Special Programs Admin., DOT

(b) In addition to complying with §172.519, the background on the POI-SON placard must be white. The symbol, text, class number and inner border must be black. The word "TOXIC" may be used in lieu of the word "POI-SON".

[Amdt. 172–123, 56 FR 66264, Dec. 20, 1991, as amended by Amdt. 172–139, 59 FR 67490, Dec. 29, 1994]

§172.555 POISON INHALATION HAZ-ARD placard.

(a) Except for size and color, the POI-SON INHALATION HAZARD placard must be as follows:



[62 FR 39409, July 22, 1997]

§ 172.556 RADIOACTIVE placard.

(a) Except for size and color, the RA-DIOACTIVE placard must be as follows:

